

## ISO 7379 12.9 PASSCHROEVEN F9 PASSING – ROESTVASTSTAAL A2

ISO 7379 12.9 HEXAGON SOCKET HEAD SHOULDER SCREWS F9 TOLLERANCE – STAINLESS STEEL A2

ISO 7379 12.9 VIS DE CENTRAGE A TETE CYLINDRIQUE A SIX PANS CREUX ET A BOUT FILETE REDUIT F9 – ACIER INOXYDABLE A2

ISO 7379 12.9 PASS-SCHULTERSCHRAUBEN MIT INNENSECHSKANT UND ANSATZSCHAFST F9 – ROSTFREISTAHL A2

	ISO	: ≈ 7379		<b>M</b> <b>RVS</b> <b>70</b>
	DIN	: -		
	NEN	: -		
	ANSI	: -		
	BS	: -		
	NF	: -		

P		0,5	0,7	0,8	1	1,25	1,5
ds (nom.)		4	5	6 <sub>1</sub>	8	10	12 <sub>1</sub>
Tolerantie f9	(max.)	3,990	4,990	5,990	7,987	9,987	11,984
	(min.)	3,960	4,960	5,960	7,951	9,951	11,941
b		7	8	9,5	11	13	16
dk (max.)		7	9	10,22	13,27	16,27	18,27
k (max.)		3	4	4,5	5,5	7	(8)9 <sub>1</sub>
s		2	2,5	3	4	5	6

d LENGTE	M3	M4	M5	M6	M8	M10
4	61044030004					
5	61044030005	61044040005				
6	61044030006	61044040006	61044050006			
8	61044030008	61044040008	61044050008	61044060008		
10	61044030010	61044040010	61044050010	61044060010	61044080010	
12	61044030012	61044040012	61044050012	61044060012	61044080012	61044100012
16	61044030016	61044040016	61044050016	61044060016	61044080016	61044100016
20	61044030020	61044040020	61044050020	61044060020	61044080020	61044100020
25	61044030025	61044040025	61044050025	61044060025	61044080025	61044100025
30	61044030030	61044040030	61044050030	61044060030	61044080030	61044100030
35						
40			61044050040	61044060040	61044080040	61044100040
45						
50			61044050050	61044060050	61044080050	61044100050
55						
60				61044060060	61044080060	61044100060
65						
70					61044080070	61044100070
75						
80					61044080080	61044100080
85						
90						61044100090
95						
100						61044100100
110						
120						61044100120

<sub>1</sub> Wijkt af van ISO 7379



## ISO 7379 12.9 PASSCHROEVEN F9 PASSING – ROESTVASTSTAAL A2

ISO 7379 12.9 HEXAGON SOCKET HEAD SHOULDER SCREWS F9 TOLLERANCE – STAINLESS STEEL A2

ISO 7379 12.9 VIS DE CENTRAGE A TETE CYLINDRIQUE A SIX PANS CREUX ET A BOUT FILETE REDUIT F9 – ACIER INOXYDABLE A2

ISO 7379 12.9 PASS-SCHULTERSCHRAUBEN MIT INNENSECHSKANT UND ANSATZSCHAFT F9 – ROSTFREISTAHL A2

	ISO	≈ 7379		<b>M</b> <b>RVS</b> <b>70</b>
	DIN	--		
	NEN	--		
	ANSI	--		
	BS	--		
	NF	--		

P		1,75	2			
ds (nom.)		16	20			
Tolerantie	(max.)	15,984	19,980			
f9	(min.)	15,941	19,928			
b		18	22			
dk (max.)		24,33	30,33			
k (max.)		(10)11,	14			
s		8	10			
<b>d</b>		<b>M12</b>	<b>M16</b>			
<b>LENGTE</b>						
6						
8						
10						
12						
16						
20		61044120020	61044160020			
25		61044120025	61044160025			
30		61044120030	61044160030			
35		61044120035	61044160035			
40		61044120040	61044160040			
45						
50		61044120050	61044160050			
55						
60		61044120060	61044160060			
65						
70		61044120070	61044160070			
75						
80		61044120080	61044160080			
85						
90		61044120090	61044160090			
95						
100		61044120100	61044160100			
110						
120		61044120120	61044160120			

1 Wijkt af van ISO 7379

