



ISO 7379 12.9 PASSCHROEVEN H8 PASSING - STAAL

ISO 7379 12.9 HEXAGON SOCKET HEAD SHOULDER SCREWS H8 TOLLERANCE – STEEL

ISO 7379 12.9 VIS DE CENTRAGE A TETE CYLINDRIQUE A SIX PANS CREUX ET A BOUT FILETE REDUIT H8 – ACIER

ISO 7379 12.9 PASS-SCHULTERSCHRAUBEN MIT INNENSECHSKANT UND ANSATZSCHAFT H8 – STAHL

		ISO	: ≈ 7379				M
		DIN	: -				St
		NEN	: -				12.9
		ANSI	: ≈ B18.3.3M				
		BS	: ≈ 4168-7				
		NF	: -				
P		0,8	1	1,25	1,5	1,75	2
ds (nom.)		6 ₁	8	10	12 ₁	16	20
Tolerantie h8	(max.)	6,000	8,000	10,000	12,000	16,000	20,000
	(min.)	5,982	7,978	9,978	11,973	15,973	19,967
b		9,5	11	13	16	18	22
dk (max.)		10,22	13,27	16,27	18,27	24,33	30
k (max.)		4,5	5,5	7	(8)9 ₁	(10)11 ₁	14
s		3	4	5	6	8	10
d	LENGTE	M5	M6	M8	M10	M12	M16
6		17117050006					
8		17117050008	17117060008				
10		17117050010	17117060010	17117080010			
12		17117050012	17117060012	17117080012	17117100012		
16		17117050016	17117060016	17117080016	17117100016		
20		17117050020	17117060020	17117080020	17117100020	17117120020	17117160020
25		17117050025	17117060025	17117080025	17117100025	17117120025	17117160025
30		17117050030	17117060030	17117080030	17117100030	17117120030	17117160030
35		17117050035	17117060035	17117080035	17117100035	17117120035	17117160035
40		17117050040	17117060040	17117080040	17117100040	17117120040	17117160040
45		17117050045	17117060045	17117080045	17117100045	17117120045	17117160045
50		17117050050	17117060050	17117080050	17117100050	17117120050	17117160050
55		17117050055	17117060055	17117080055	17117100055	17117120055	17117160055
60		17117050060	17117060060	17117080060	17117100060	17117120060	17117160060
65		17117050065	17117060065	17117080065	17117100065	17117120065	17117160065
70		17117050070	17117060070	17117080070	17117100070	17117120070	17117160070
75		17117050075	17117060075	17117080075	17117100075	17117120075	17117160075
80		17117050080	17117060080	17117080080	17117100080	17117120080	17117160080
85							
90		17117050090	17117060090	17117080090	17117100090	17117120090	17117160090
95							
100		17117050100	17111060100	17117080100	17117100100	17117120100	17117160100
110							
120				17117080120	17117100120	17117120120	17117160120

¹ Wijkt af van ISO 7379



ISO 7379 12.9 PASSCHROEVEN H8 PASSING - STAAL

ISO 7379 12.9 HEXAGON SOCKET HEAD SHOULDER SCREWS H8 TOLLERANCE – STEEL

ISO 7379 12.9 VIS DE CENTRAGE A TETE CYLINDRIQUE A SIX PANS CREUX ET A BOUT FILETE REDUIT H8 – ACIER

ISO 7379 12.9 PASS-SCHULTERSCHRAUBEN MIT INNENSECHSKANT UND ANSATZSCHAFT H8 – STAHL

	ISO	: ≈ 7379		M St 12.9
	DIN	: -		
	NEN	: -		
	ANSI	: ≈ B18.3.3M		
	BS	: ≈ 4168-7		
	NF	: -		

P		2,5				
ds (nom.)		24				
Tolerantie	(max.)	24,000				
h8	(min.)	23,967				
b		27				
dk (max.)		36				
k (max.)		16				
s		12				

d	M20					
LENGTE						
6						
8						
10						
12						
16						
20	17117200020					
25	17117200025					
30	17117200030					
35	17117200035					
40	17117200040					
45	17117200045					
50	17117200050					
55	17117200055					
60	17117200060					
65	17117200065					
70	17117200070					
75	17117200075					
80	17117200080					
85						
90	17117200090					
95						
100	17117200100					
110						
120	17117200120					

¹ Wijkt af van ISO 7379

